

Life Support Gas Cylinders - Aluminum

Specifications

Sales Part Number	Service Pressure		Air Capacity		Outside Diameter		Overall Length		Empty Weight		Min. Internal Volume		Min. Water Weight		Thread Size UNF
	psi	bar	cu ft	liters	in	mm	in	mm	lbs	kg	cu in	liters	lbs	kg	
L007	2216	153	7.2	204.4	4.38	111.13	9.3	235.0	3.6	1.6	83	1.4	2.99	1.36	0.750-16 UNF-2B
L008	2216	153	8.0	226.6	4.38	111.13	10.0	253.2	3.8	1.7	92	1.5	3.32	1.50	0.750-16 UNF-2B, 0.875-14 UNF-2B
L013	3000	207	13.2	375.0	5.25	133.35	10.0	254.0	6.6	3.0	116	1.9	4.18	1.90	0.750-16 UNF-2B
L13S	3000	207	13.2	375.0	4.38	111.13	13.1	333.4	6.0	2.7	116	1.9	4.18	1.90	0.750-16 UNF-2B
L014	3000	207	13.2	375.0	5.25	133.35	10.0	254.0	6.9	3.1	116	1.9	4.18	1.90	0.625-18 UNF 2-B
L015	3000	207	15.3	432.6	4.38	111.13	14.6	371.5	6.6	3.0	134	2.2	4.82	2.19	0.750-16 UNF-2B
L045	2216	153	44.9	1272.2	6.75	171.45	20.9	530.2	16.8	7.6	517	8.5	18.63	8.45	0.750-16 UNF-2B, 1.125-12 UNF-2B

3016 Kansas Avenue, Riverside, CA 92507 USA,
Tel: (909) 684 5110 or (800) 764 0366 Fax: (909) 781 6598

© 2003 Luxfer Inc.

